

## Transient Limitor for 72V, 96V, 110V 1.8kV & 8.4kV Spike Suppressor EN50155 Metallic Case



- Spike suppressor module
  - EN50155 level 1.800V
- Transient suppressor module
  - EN50155
- Input reverse polarity protection
- High efficiency (98%)
- Power range : from 4W to 75W
- Integrated EMI filter EN55022 class A
- Inhibition function
- RoHS process

### 1-General

The Gaia Converter limiter LGDSI-75 Series designates an active power adaptor module designed to protect electrical systems against fast transient and high spike levels that can occur from an input bus line with no voltage stabilization devices.

The LGDSI-75 delivers an adapted output voltage compliant with Gaia Converter DC/DC range of modules. This line of module is optimized to provide high efficiency up to 98% over the whole power range between 4W and 75W power.

The module includes also an EMI filter to provide compliance with EN55022 Class A together with GAIA Converter DC/DC modules.

The module is manufactured in a fully automated process to guarantee high quality. Each module is tested with a Gaia Converter automated test

equipment.

The LGDSI-75 features 2 modes of operations as follow :

- **Normal operation :**

Normal operation occurs when input bus line is in steady state permanent range. The LGDSI-75 is then operating in steady transparency state providing an output with a typical 1,5V drop-out voltage.

- **Transient and spikes operation**

The LGDSI-75 can sustain both :

- transient during 1s according to EN50155 requirements,
- high spike levels up to 1.8kV with 5 Ohms impedance and 8,4kV with 100 Ohms impedance to meet international input bus standards of EN50155.

5

### 2-Product Selection

Single output model : LGDSI - 75 -  -

Input Voltage Range
Permanent
Q : 43-154 VDC

Output
K

### 3- Modes of Operation


#### 3-1 LGDSI-75 Modes of Operation

The LGDSI-75 series features 3 modes of operations detailed hereafter and illustrated by the 2 figures which depict the transfer functions

- **Power fail operation :**  
An undervoltage lock-out stops operation for input voltage below the low line operation threshold (typically 10Vdc).

- **Normal operation :**  
During normal operation the module is operating in steady transparency state.

- **Transient and spike operation :**  
The LGDSI-75 series can sustain input transient and spike describe in section 4 by a clamping input system.



## 4- Electrical Specifications

Data are valid at +25°C, unless otherwise specified.

Parameter	Conditions	Limit or typical	Units	LGDSI-75-Q-K
<b>Input</b>				
Compatible with nominal battery voltage	Full temperature range	Nominal	VDC	72 / 96 / 110
Limiter start up voltage	Full temperature range	Maximum	VDC	10
Permanent input voltage range	Full temperature range	Min. - Max.	VDC	43-154
Transient input voltage	Full temperature range Full load meet standards EN50155, Transient 1 sec. Transient 100 ms	Maximum	VDC/s	165/1
		Maximum	VDC/ms	176/100
Spike input voltage limit (Direct spike and indirect coupled spike)	Full temperature range Full load meet standard  EN50155	Level A	VDC	(5/50μs, 5 Ohm or 100 Ohm)
		Level B	VDC	(0,05/0,1μs, 100 Ohm)
Current in inhibit mode	No load to full load	Maximum	mA	10
<b>Output</b>				
Nominal output voltage in normal operation	In permanent input voltage mode	Maximum	VDC	U <sub>i</sub> - 1
		Minimum	VDC	U <sub>i</sub> - 2
Output voltage in limitation operation	In transient input voltage mode	Maximum	VDC	152
Efficiency	At indicated nominal input Full load	Typical	%	96% at 72V input 97% at 96V input 98% at 110V input
Output power range	Full temperature range For 96V and 110V input For 72V input	Maximum	W	75
		Maximum	W	50

## 5- Functional Characteristics

Characteristics	Conditions	Limit or typical	Performances
Isolation voltage	Between any pin	Typical	No isolation
Input reverse polarity protection	Reverse polarity	Maximum	Maximum permanent input voltage

## 6- Thermal Characteristics

Characteristics	Conditions	Limit or typical	Performances
Operating ambient temperature range	Ambient temperature *	Minimum Maximum	- 40°C + 71°C
Operating case temperature range	Case temperature	Minimum Maximum	- 40°C + 95°C
Storage temperature range	Non fonctionning	Minimum Maximum	- 40°C + 105°C

Note \* : The upper temperature range depends on configuration, the user must assure a max. case temperature of + 95°C (See Application Notes : Ambient versus case temperature).

## 7- Reliability Characteristics

Characteristics	Conditions	Temperature	Performances
Mean Time Between Failure (MTBF) According to MIL-HDBK-217F	Ground fixed (Gf)	Case at 40°C Case at 70°C	2 500 000 Hrs 1 100 000 Hrs

## 8- Environmental and Electromagnetic Interference Qualifications

Characteristics	Conditions	Severity	Test procedure
Humidity	Damp heat Temperature	93 % H.R 56 Days 40°C	IEC 68-2-3
Vibration (Sinusoidal)	Number of cycle Frequency Amplitude /acceleration	10 cycles in each axis 10 to 60 Hz/ 60 to 2000 Hz 0.7 mm/10 g	IEC 68-2-6
Shock (Half sinus)	Number of shocks Peak acceleration Duration	3 shocks in each axis 100 g 6 ms	IEC 68-2-27
Bump (Half sinus)	Number of bumps Duration Peak acceleration	2 000 Bumps in each axis 6 ms 25 g	IEC 68-2-29
Conducted noise emission	Frequency range 150 KHz to 30 MHz	Class A compliance together with GAIA Converter DC/DC modules stand alone	EN55022
Radiated noise emission	Frequency range 30 MHz to 1.000 MHz	Class A compliance together with GAIA Converter DC/DC modules stand alone	EN55022
Electrical discharge susceptibility	Air discharge level +/-4 KV Contact discharge level +/- 2KV Air discharge level 8 KV Contact discharge level 4 KV	sanction A sanction A sanction B sanction B	EN55082-2 with : EN61000-4-2 IEC 801-2
Electrical field susceptibility	Antenna at 1 m Wave form : AM modulated 80 %, 1KHz Test : 26 KHz to 1 GHz	Value 10V/m	EN55082-2 with : EN61000-4-3 IEC801-3
Electrical fast transient susceptibility	Level 1 : 0.5 KV Level 3 : 2 KV	sanction A sanction B	EN55082-2 with : EN61000-4-4 IEC801-4
Surge Susceptibility	Level 4	See section 4	EN61000-4-5 EN50155

## 9- Application Notes

### 9-1 Reverse Polarity Compatibility


The LGDSI-75 integrates a reverse polarity protection connected directly on Vin (pin 1).

### 9-2 On/Off Function

The control pin 2 (On/Off) can be used for applications requiring On/Off operations. By using an open collector command with a transistor Q referenced to the terminal Gi :

- A Level 1 on command disables the converter,
- A Level 0 an command or no connection / high impedance enables the converter.


In off mode, the current consumption stays below 10mA.



### 9-3 Typical Schematic


The LGDSI-75 is suitable to be used with several DC/DC GAIA converter modules in a parallel configuration as follow.

The LGDSI-75-Q-K can work in conjunction with GAIA Converter Q input (36-140V) and R input (12-160V) series for applications using 72V, 96V or 110V input batteries.



## 10- Dimensions

Dimension are given in mm (inches). Tolerance : +/- 0,2 mm (+/- 0.01 ") unless otherwise indicated.  
Weight : 28 grams (1 Ozs) max.



Pin dimensions :  $\varnothing$  0,73 mm (0.03 ")

## 11- Materials

Case : Metallic black anodized coating.


Pins : Plated with pure matte tin over nickel underplate.

## 12- Product Marking

Upper face : Company logo.

Side face : Module reference, option, date code : year and week of manufacturing.

## 13- Connections



Bottom view

Pin	LGDSI-75
1	+ Input (Vi)
2	On / Off
3	- Input (Gi)
4	Common (Go)
5	Output (Vo)



Represented by :